

Technical Data Sheet **W350**

Quick Drying Urethane-Acrylate Woodrepair - Ultimate Strength

- 30 minutes drying time
- Paintable with acrylic & alkyd paints
- High durability

Description	2 part Urethane-Acrylate based woodrepair paste.
Usage	For interior and exterior use. For repairing damaged wood, small repairs.
Preparation	Substrate should be clean, dry and free from all dust and loose material.
Application	Mix both components in a 1:1 ratio (on a volume base) to a homogeneously coloured paste. For small repairs.
Drying time	Drying time before sanding / painting: minimum 30 minutes. Drying time depends on temperature, humidity and size of repair.
Packaging	600 ml cartridge set (2 x 300 ml).
Storage	Store under dry conditions away from frost.
Remarks	- Ideally suitable for small repairs. - Do not mix more than can be applied within 10 minutes. - Compatible with W340 primer but use of the primer is not required. - For larger repairs W360 (medium size) or W370 (large and complex repairs) is recommended.

Technical data

Density	: 1.56 kg/L (mixed)
Color	: light beige (mixed)
Worklife at 20°C	: ca. 12 minutes
Drying Time	: 30 minutes at 20°C and 60% relative humidity
Application temp	: minimum 2°C maximum 30°C
pH value	: not applicable
Grainsize	: 85 µm
Hardness	: 55-65 Shore D
Min repair depth	: none
Max repair depth	: 10 mm
VOC	: 54 g/L (mixed)